



Steam CLEANERS

DIESEL, NATURAL GAS OR LP STEAM CLEANERS



MODEL	122	240	181	241	301
STEAM CAPACITY*	120 GPH	240 GPH	180 GPH	240 GPH	300 GPH
WASH CAPACITY*	N/A	N/A	N/A	N/A	N/A
STEAM PRESSURE*	400 PSI	400 PSI	250 PSI	250 PSI	400 PSI
WASH PRESSURE*	N/A	N/A	N/A	N/A	N/A
PUMP	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath
MOTOR**	3/4 HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	3/4 HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	4 HP, 230 V, 1 PH
COIL*** (STEEL PIPE)	126', 5/8" ID, Schedule 40	245', 5/8" ID, Schedule 40	243', 5/8" ID, Schedule 40	420', 5/8" ID, Schedule 40	515', 3/4" ID, Schedule 40
BURNER, OIL, PRESSURE ATOMIZING, AUTO, IGNITION	Kerosene, #1 or #2 Diesel 392,000 BTU	Kerosene, #1 or #2 Diesel 784,000 BTU	N/A	N/A	N/A
BURNER, GAS, NATURAL ASPIRATING, NATURAL OR L.P. GAS	N/A	N/A	490,000 BTU	650,000 BTU	880,000 BTU
FUEL CONSUMPTION	2.80 GPH	5 GPH	Nat.-476 Cu. Ft. per Hr. L.P.-5.3 GPH	Nat.-620 Cu. Ft. per Hr. L.P.-7 GPH	Nat.-990 Cu. Ft. per Hr. L.P.-11.3 GPH
TANK CAPACITY	Fuel 12 Gal.	Fuel 10 Gal.	N/A	N/A	N/A
WAND	Open-Standard	Open-Standard	Open-Standard	Open-Standard	Trigger-Standard
HOSE	3/8" x 50"	3/8" x 50"	3/8" x 50"	3/8" x 50"	1/2" x 50"
CHEMICAL	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
FLOAT TANK	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
TEMPERATURE CONTROL	Standard	Standard	Standard	Standard	Standard
WHEELS	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	N/A	N/A	N/A
DIMENSIONS	L-34" x H-42" x W-27 1/2"	L-57" x H-45" x W-29"	L-48" x H-54" x W-22 1/2"	L-50" x H-61" x W-24"	L-56" x H-71" x W-30"
WEIGHT	400 lbs.	525 lbs.	600 lbs.	780 lbs.	905 lbs.

APPLICATIONS

- Engine and transmission grease
- Heavy construction equipment
- Tanker, vat or barrel cleaning
- Cold weather cleaning
- Surface preparation for maintenance and painting

DIESEL, NATURAL GAS OR LP GAS FIRED

- Oil fired models have pneumatic wheels for easy transport
- Gas fired steamers designed for permanent installation

With up to 300 degrees of steam cleaning power, Alkota's diverse range of steam cleaners give you the power to polish through your toughest projects.



Model 240



Model 301



Model 122

* Gallonage and pressure may vary +/- 5% due to manufacturing tolerance in components.

**Special voltages upon request. Gallonages and pressures may be less on 3 phase current.

***ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable.

New!
Model 401



GAS *Fired* SERIES

NATURAL & LP GAS INDUSTRIAL STEAM CLEANER

MODEL	401
STEAM CAPACITY	400 GPH
STEAM PRESSURE	400 PSI
PUMP	Triplex, Oil Bath
MOTOR	4HP, 230 Volt, 1 PH
COIL	483, 3/4"ID, Sched. 80
BURNER, GAS, NATURAL ASPIRATING, NAT. OR LP GAS	1,200,000 BTU/hr
FUEL CONSUMPTION	Nat. - 1200 Cu. Ft/hr L.P. - 13.26
WAND	Trigger, Standard
HOSE	1/2"x50'
CHEMICAL	Precise Metered
FLOAT TANK	Stainless Steel
TEMPERATURE CONTROL	Standard
DIMENSIONS	L-75", W-32", H-70"
WEIGHT	1760 lbs.

