



# GAS *Engine* SERIES

SELF-CONTAINED HOT WATER PRESSURE WASHERS





## PAINTED MODELS

MODEL	4355V-P	5305EAD-P	5355E-P	5405E-P	5505J-P	8355V
<b>GPM</b>	3.8 GPM	5 GPM	5 GPM	4.5 GPM	4.5 GPM	8 GPM
<b>PSI</b>	3500 PSI	3000 PSI	3500 PSI	4000 PSI	5000 PSI	3500 PSI
<b>ENGINE</b>	14 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	23 HP, Vanguard, Electric Start, Belt Drive	35 HP, Vanguard, Electric Start, Belt Drive
<b>BURNER BTU</b>	350,000	350,000	350,000	350,000	350,000	620,000
<b>BURNER VOLTAGE</b>	12 Volt	12 Volt	12 Volt	12 Volt	12 Volt	120 Volt

## GAS ENGINE FEATURES

- No electricity needed
- Automatic ignition
- Heavy steel construction
- Oil bath pumps with ceramic plungers
- High efficiency coils
- Stainless steel reservoir
- Easy access to controls

## STAINLESS STEEL MODELS

MODEL	3255****	4355-H****	4405E****	4405EB	4405-F****	4405G****	5305EA****
<b>GPM</b>	3 GPM	4 GPM	4 GPM	4 GPM	4 GPM	4 GPM	5 GPM
<b>PSI</b>	2500 PSI	3500 PSI	4000 PSI	4000 PSI	4000 PSI	4000 PSI	3000 PSI
<b>ENGINE</b>	9 HP, Honda, Recoil, Belt Drive	13 HP, Honda, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive	16 HP, Vanguard, Electric Start, Belt Drive
<b>BURNER BTU</b>	230,000	230,000	350,000	350,000	230,000	350,000	350,000
<b>BURNER VOLTAGE</b>	12 Volt	12 Volt	12 Volt	115 Volt	12 Volt	12 Volt	12 Volt

MODEL	5305EB****	5305A****	5355J****	5355JB****	5405****	5505J****	5505E****
<b>GPM</b>	5 GPM	Wash: 5 GPM Steam: 2.5 GPM	5 GPM	5 GPM	4.5 GPM	4.5 GPM	4.8 GPM
<b>PSI</b>	3000 PSI	Wash: 3000 PSI Steam: 250 PSI	3500 PSI	3500 PSI	4000 PSI	5000 PSI	5000 PSI
<b>ENGINE</b>	16 HP, Vanguard, Electric Start, Belt Drive	18 HP, Vanguard, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive	20 HP, Honda, Electric Start, Belt Drive	20 HP, Kohler Command, Belt Drive	23 HP, Vanguard, Electric Start, Belt Drive	25 HP, Kohler, Overhead Valve, Oil Alert, Belt Drive
<b>BURNER BTU</b>	350,000	380,000	350,000	350,000	560,000	350,000	560,000
<b>BURNER VOLTAGE</b>	115 Volt	115 Volt	12 Volt	115 Volt	115 Volt	12 Volt	115 Volt

MODEL	8305****	10255	10255H	10305
<b>GPM</b>	8 GPM	10 GPM	10 GPM	10 GPM
<b>PSI</b>	3000 PSI	2500 PSI	2500 PSI	3000 PSI
<b>ENGINE</b>	25 HP, Kohler, Overhead Valve, Oil Alert, Belt Drive	25 HP, Kohler, Overhead Valve, Electric Start, Oil Alert, Belt Drive	21 HP, Honda, Overhead Valve, Electric Start, Belt Drive	35 HP, B&S Vanguard, Overhead Valve, Electric Start, Belt Drive
<b>BURNER BTU</b>	560,000	780,000	780,000	780,000
<b>BURNER VOLTAGE</b>	115 Volt	115 Volt	115 Volt	115 Volt

Call your local distributor or email sales@alkota.com for a complete specification chart.

### English to Metric Conversion

1 gallon/minute = 3.78 liters/minute  
 1 horsepower = .746 watts  
 100 PSI = 7.03 Kg/cm<sup>2</sup>  
 1 foot = .3048 meters  
 1 inch = 2.54 centimeters  
 1 pound = .45359 kilograms

\* Gallonage and pressure may vary +/- 5% due to manufacturing tolerance in components.

\*\*Batteries not included.

\*\*\*\* All models available ETL approved to UL1776 and CSA b140.11-M89 specifications. Specifications subject to change without notice.

